




The STEYR AUG A3 modular weapon system is the latest result of the continued development of the world renowned STEYR AUG rifle series.

The STEYR AUG A3 design is also based on modular system components, which can be configured from one variant to another quickly and easily, without tools, and at unit level, in order to meet a wide range of future weapon requirements.

The "Bull Pup" design maintained its short overall length, without influencing the barrel length, to meet or exceed, required accuracy standards. The STEYR AUG A3 features a number of Picatinny rails (Mil. Std. 1913 rails), which allow the quick and easy mounting of various accessories, such as illumination and target acquisition devices, including a variety of optics or night vision devices.

Due to its utmost flexibility design concept, the STEYR AUG A3 is a state-of-the-art, multipurpose assault rifle, for day and night operations. Armed and special forces in about 35 countries in the whole world are trusting in the STEYR AUG





## **STEYR AUG A3 SF**

## **SPECIFICATIONS**

Caliber	5,56x45 mm
Rate of fire	Automatic fire: 680-750 rpm
Barrel groups	407 mm (16") standard, interchangeable, 365 mm (14,5"), 508 mm (20") With gas regulator
	Cold hammer forged, chrome-lined bore including chamber. Folding grip with locator-recesses for button-switch (LLM)
Weight empty	3,970 kg Std configuration (407 mm/16" bbl)
Overall length	715 mm / 28,2"
Overall height	232 mm / 9"
•	Detachable, synthetic (transparent) staggered box type.
Magazine weight	
Magazine weight	0,13 kg 30 rounds, 42 rounds (optional)
Magazine capacity Action	Gas-operated. Gas regulator with two action settings for firing,
ACTION	to guarantee proper function under all conditions.
Trigger	"Pull through" trigger system. Fires semi automatic when pulled halfway to a clearly felt point, fires fully automatic when pulled fully back.
Trigger mechanism	Synthetic (except for springs, steel bearing pins and catch holding open).
Safety	Lateral push-through type locks trigger.
Housing group	With integrated 1.5x optical sight, ring reticule, optics-housing with Mil.Std.1913 accessory rails left/right/top, additional short rail above trigger/right side, foldable cocking handle
Stock	Synthetic, olive-drab or black. External bolt release.
Bolt	Fixed locking turn bolt, with seven locking lugs. The rifle can be changed easily from right to left hand ejection, simply by flipping the ejection port lid to the other side and installing a left hand bolt (no tools required).
Add on	Red dot sights, LLM, suppressor

